

4K-Remote-Kamera mit NDI I HX-Unterstützung.

AW-UN70

4K-Remote-Kamera mit NDI I HX-Unterstützung.



KEY FEATURES

- Integrierte Unterstützung von NDI über NDI|HX
- 20-facher optischer Zoom (+30-facher iZoom und 12-facher digitaler Zoom)
- 1/2,3-Typ MOS-Sensor
- PoE+ für Strom, Steuerung, Streaming und Tally über ein Kabel
- 1300 Zeilen horizontale Auflösung (UHD)

SPECIFICATIONS

Color	Black (K) or White (W)
Sensor	1/2.3 inches MOS
Optical Zoom	20x
i.Zoom	30x
Digital Zoom	12x
FOV (Horizontal)	65.1° (W) - 3.2° (T)
FOV (Vertical)	39.5° (W) - 1.8° (T)
FOV (Diagonal)	72.4° (W) - 3.7° (T)
Focus	Auto / Manual
Horizontal Resolution	1300 Lines (UHD)
Minimum Illumination	0.35 lx
Gain	0 dB - 48 dB
Power	PoE+ or AC
Weight (kg)	Approx. 1.5 kg
Weight (lbs.)	3.30 lbs
Installation	Tripod, Wall*2, Ceiling
Mount Position	Invertible
Standard Warranty	1 Year

Pan Range ±175 degrees

Tilt Range	-30 to 90°
Pan / Tilt Speed	300°/s (Preset) 90°/s (M)
Operation Noise	NC35 or Less
LAN with built-in ND HX*1	<input checked="" type="checkbox"/>
3G-SDI	<input checked="" type="checkbox"/>
HD-SDI	<input checked="" type="checkbox"/>
SD-SDI	-
HDMI	<input checked="" type="checkbox"/>
Composite	-
USB	<input checked="" type="checkbox"/>
Output Format	2160/29.97p*3, 1080/59.94p, 1080/29.97p, 1080/59.94i, 1080/29.97PsF, 720/59.94p, 2160/25p*3, 1080/50p, 1080/25p, 1080/50i, 1080/25PsF, 720/50p
Browser (PC/Mac/Mobile) via IP	<input checked="" type="checkbox"/>
Live Production Center (Streaming Switcher/Controller)	AV-HLC100
Wide-Angle Tablet Control	AW-HEA10
IR Remote Control	AW-RM50
Compact Controller	AW-RP50
Full-Size Controller	AW-RP120
Remote Operation Panel	AK-HRP200
Compact Live Switcher	AW-HS50N
IP Live Preview	<input checked="" type="checkbox"/>
Simultaneous Multi-Stream	<input checked="" type="checkbox"/>
Image Stabilization	Optical, Hybrid O.I.S. (FHD)
Night Mode (for IR)	<input checked="" type="checkbox"/>
Dynamic Range Stretch (DRS)	<input checked="" type="checkbox"/>
Audio Input / Embedding	<input checked="" type="checkbox"/>
Color Temperature Adjustment	<input checked="" type="checkbox"/>
Presets	Up to 100
microSD Card Recording	<input checked="" type="checkbox"/>
High Dynamic Range (HDR)	<input checked="" type="checkbox"/>
Fanless Design	<input checked="" type="checkbox"/>
ND Filters	<input checked="" type="checkbox"/>
Genlock	<input checked="" type="checkbox"/>
Advanced Color Adjustment	-
Digital Noise Reduction (DNR)	<input checked="" type="checkbox"/>
Note	*1: This product is compatible with ND HX technology of NewTek, Inc. *2: With appropriate right angle wall mount, available locally *3: HDMI output only. *4: When either 480/59.94p(i) or 576/50p(i) is selected, the output formats are delivered as follows: P signal for HDMI output and I signal for SDI output.

URL: https://business.panasonic.de/professional-kamera/full_hd_remote_camera_with_built-in_network-device-interface_ndi_support/aw-un70-0

CONTACT

Web: <https://business.panasonic.de/professional-kamera/contact-us>